


# The KATRIN cryogenic system


**Steffen Grohmann**

3<sup>rd</sup> ASPERA Technology Forum «Industry meets academia», Darmstadt, March 13-14, 2012


INSTITUTE FOR TECHNICAL PHYSICS (ITEP)



# The beamline of KATRIN



# Overview of the KATRIN cryogenic system



# The KATRIN helium refrigerator


- Adapted standard refrigerator

- Linde TCF50
  - Additional beam tube cooling circuit with 6 g/s He @ 25/117 K

- Cooling power


~450 W @ 5 K / 5 bar

- Connection to existing helium purification plant



490 W measured during acceptance tests


# KATRIN cryogenic transfer line



- Mixing of 5 K and 300 K helium in the valve boxes for cool-down
  - Better operation with separate cool-down line from the refrigerator

# KATRIN cryogenic transfer line

- Process design/dimensioning by KIT
- User specification with geometric constraints, conceptual design
- Detailed design by supplier
- Design verification and manufacturing release by customer
- Manufacturing, testing, installation, commissioning executed in the supplier's responsibility
  - Leak testing!
- Successful project completion within the planned schedule and cost frame



# Principle of the helium bath cryostats


- Internal reservoir for standalone operation (48 h)

## Valve functions

- V1: Bypass
- V2: Return valve
- V3: J-T valve
- V4: Cool-down
- V5: LHe supply


## Stationary operation

- $p_{\text{Sat}} = 1.3 \text{ bar}$
- $T_{\text{Sat}} = 4.5 \text{ K}$




# Safety concept for helium cryostats

Unintended use	Impermissible error range
Normal use	Acceptable error range
	Acceptable range




	Damage limitation level
Rupture disk Safety relief valve	Protection level
Pressure switch (hard wired) PLC PLC	Monitoring level
Controller	Operating level






# Cooling of the KATRIN tritium source

- Requirements for the 10 m beam tube
  - Temperature stability  $30 \text{ K} \pm 0.03 \text{ K/h}$
  - Temperature homogeneity  $30 \text{ K} \pm 0.03 \text{ K}$  over 95 % tube length




# The KATRIN Demonstrator inside TLK




# Measured temperature stability

## Vapor pressure measurement



## Resolution



Date of measurements: February 19, 2011

# Recommendations / lessons learned

## ■ Refrigerator

- Project realization straightforward
  - Functional user specification
- Commissioned long before required (→ warranty)
- Plan separate cool-down line for magnet cryostats

## ■ Cryogenic transfer system

- Process engineering by customer, detailed design by supplier
  - Conceptual design part of user specification
- Importance of project management and QA
  - Standards, documentation, testing → Round table
- Project realization within schedules and cost frames

# Recommendations / lessons learned

## ■ Cryostats

- Think carefully about the safety concept (pressure rating)!
- Large LHe reservoirs inside the cryostats have increased the complexity of the cryostat design (space limitations)
- **Functional user specifications are problematic!**
- Long design phases with several iterations
- Cryogenic know-how on the customer side is vital (process engineering)
- Importance of project management and QA
  - Standards, documentation, testing → Round table
- Large underestimation of efforts by both the project and the suppliers