



H2020 McSAFER: High-Performance Advanced Methods and Experimental Investigations for the Safety Evaluation of Generic Small Modular Reactors

20. IAEA TWG FPT Meeting (EVT2105273)

V. H. Sanchez-Espinoza

H. Suikkanen, V. Valtavirta, M. Bencik, S. Kliem, C. Qeral, A. Farda, P. Smith, P. Van Uffelen, M. Seidl, Ch. Schneidesch, D. Grishchenko, H. Lestani

Vienna, April 6th. 2022



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.

- Goals and scientific approach
- Partners, budget
- Work packages
- Selected SMR-designs
- Challenges and solution approach
- Education & Training, Dissemination



Technical Goals & scientific approach

Technical goals:


- Advance the safety research for water cooled SMR
 - Perform key experiments relevant for SMR-safety (core, helical HX) at EU-facilities (COSMOS-H, MOTEL, HWAT)
 - Develop, improve, validate simulation tools for safety evaluations of SMRs
 - Demonstrate advantages of advanced (multiphysics /multiscale) tools compared to legacy ones
- Apply simulation tools to four SMR-designs (F-SMR, CAREM, NuScale, SMART)

Scientific approach:

- Combine experimental investigations with numerical tools for safety
- Consider different SMR-designs:
 - Natural circulation: CAREM, NuScale
 - Forced convection: F-SMR, SMART
 - Core design: **square** (F-SMR, SMART, NuScale) and **hexagonal** (CAREM) fuel assemblies
 - Etc.



Partners and Budget



Partners: 13

- **R&D:** CEA, VTT, HZDR, UJV, JRC KA, CNEA
- **Universities:** LUT, UPM, KIT, KTH
- **Industry:** Jacobs, TRACTEBEL, PEL

Budget:

- Total: 4 045 133.75 €
- EC-contribution: 95 %
(3 995 982.50 €)
- In-Kind: 5 %




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.




20. IAEA TWG FPT Meeting. April, 5-6. 2022

McSAFER: Work Packages, Interactions



McSAFER: Work Package Structure



McSAFER: Management Structure




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.




20. IAEA TWG FPT Meeting. April, 5-6. 2022

SMR-Designs under investigations: CAREM



RPV and Secondary Side


IAEA-2012: Status of Small and Medium sized Reactor Designs. A supplement to the IAEA Advanced Reactor Information System (ARIS)



RPV and Internals

Ch. Marcel; CAREM-25: A safer innovative Small Nuclear Power Plant. Nuclear Revista Espanha 1, Enero 2017.

- 61 FA @163 pins (1.4 m)
- Some FA with BP (6-12)
- 25 control FA
- U-235 enrichment: 1.8 to 3.1 %



CAREM-Like core




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.





20. IAEA TWG FPT Meeting. April, 5-6. 2022

SMR-Designs under investigations: FSMR




RPV and Secondary Side

J. Chenais, M. Brun; SMR/The French Approach. IAE SMR Technical working group meeting. Vienna, July 8-11. 2019



RPV and Internals



FSMR Core

- 57 standard FA 17x17-24-1
- All FA with control rods (AIC)
- Gd-rods (6-10 %)
- Active height: 1.6 m
- 4 FA designs (heterogeneous)
- U225 enrichment: 5 zones (3.5-4.95 %)




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.





20. IAEA TWG FPT Meeting. April, 5-6. 2022

SMR-Designs under Investigation: NuScale



Integral Plant



RPV and Internals

- 37 FA 17x17-24-1
 - Active height: 2 m
 - GD-rods (16)
 - U235 enrich: 1.5 -4.55 %
- Control rods design:
 - Axial varying materials: AIC, B4C

	A	B	C	D	E	F	G
1			C01	B02	C01		
2		C02	B01	A01	B01	C02	
3	C01	B01	A02	A01	A02	B01	C01
4	B02	A01	A01	C03	A01	A01	B02
5	C01	B01	A02	A01	A02	B01	C01
6		C02	B01	A01	B01	C02	
7			C01	B02	C01		

Core

NuScale Plant Design Overview Revision 2. NP-ER-0000-1198-NP. September 16 2013. NuScale Power LLC.



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022

Challenges I: Safety relevant TH Phenomena

- Experimental data exist but proprietary (SMR developers)
- Public SMR-specific data for research community needed e.g.
 - Cross flow in the core
 - Helical HX
 - Transition from
 - Forced to natural convection
 - Natural to forced convection
 - Safety parameters like
 - CHF
 - 3D flow inside the RPV
 - Effectiveness of PRHRS
 - Stability of natural convection flow
- Data need for code validation



McSAFER Solution Approach:

- COSMOS-H experimental program:
 - Fundamental HT, boiling, CHF
- HWAT experimental program:
 - System behavior under natural circulation
 - Transition to forced convection
 - Transition to natural convection
- MOTEL experimental program:
 - Helical HX heat transfer, pressure drop
 - Cross flow in the core

WP2: Key Experimental Investigations & Validation



- **Fundamental heat transfer tests for SMR at KIT COSMOS-H facility**
 - Investigation of boiling under forced convection up to CHF in rod geometries



COSMOS-H test Facility (KIT)

- **SMR thermal hydraulic experiments at LUT MOTEL facility**
 - Representing iPWR SMR operating with natural circulation and equipped with a helical steam generator



MOTEL Facility (LUT)

- **Tests at the KTH HWAT facility for SMR**
 - Forced/natural circulation test, investigation of heat transfer including CHF in condition relevant for SMRs



HWAT Multisensor Probe Unit (KTH)



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022



COSMOS-H Facility (KIT): Experiments and Status



- Two test series: **single rod**, **5 rod bundle**
- Test matrices defined based on review of various SMRs
- Stepwise power increase up to CHF
- Optical access (LDA, high-speed camera)
- Facility commissioning and first tests approaching**

Parameter	Value
Working fluid	Deminerlized water
Max system pressure / temperature test loop	17 MPa @ 370°C
Range of mass flow rate	0.5 – 10 m³/h
Thermal power facility	~ 2 MW
Thermal power for test section	600 kW DC
Required time for load shedding	0.15 s
Heated length	1 m

Key data of the test facility



Cross-sectional view of the two planned test arrangements



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



MOTEL Test Facility (LUT): Experiments and Status




- Two test series: **SG performance**, **core cross flow**
- SG tests completed, total of 8 steady state steps
- Core cross flow tests with uneven radial power distributions under planning




CHARACTERISTICS	MOTEL
Total height [m]	7.4
Outside diameter of main vessel [mm]	711
Maximum primary/secondary pressure [bar]	40
Maximum primary/secondary temperature [°C]	250
Number of helical coil steam generator tubes	16
Maximum core heating power [kW]	990
Number of heater rods	132
Heated length of heater rods [mm]	1830
Diameter of heater and measurement rods [mm]	19.05

CHARACTERISTICS	HELICAL COIL STEAM GENERATOR
Number of tubes / tube bundles	16 / 4
Tube outer diameter / wall thickness [mm]	15 / 1.0
Tube lengths [m]	20.0 / 21.7 / 23.4 / 25.1
Helical coil loop diameters [mm]	515 / 560 / 605 / 650
Total heat transfer area [m ²]	17.0



MOTEL Core: Heater Segments




Averaged axial temperature profiles of all steam generator tubes with different core power levels



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



HWAT Test Facility (KTH): Experiments and Status




HWAT Test Loop


- Two test series:
 - forced circulation steady state,
 - transition from forced to natural circulation transients
- Movable multi-sensor probe equipped with optical void fraction sensor and local velocity sensor
- First test series being completed, planning for series 2 initiated

Parameter	Value
Maximal power, MWth	1
Maximal mass flow rate, Kg/s	1
Maximal pressure, MPa	25
Maximal coolant temp, °C	350
Effective loop height, m	8.8

Key Test Parameters



HWAT experimental setup for transient tests under natural circulation



HWAT: GOTHIC Representation (Pre- and post-test analysis)



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



Validation of Thermal Hydraulic Codes using McSAFER-Data



- CFD-Codes

- ANSYS CFX (KIT)
- OpenFOAM (LUT)
- FLUENT (UJV)

- Subchannel Codes

- Subchanflow (KIT)
- VIPRE (UJV)
- COBRA-TF (TRACTEBEL)

- System Thermal hydraulic Codes

- TRACE (KIT, UPM, KTH)
- APROS (LUT)
- RELAP5-3D (UJV)
- GOTHIC (KTH)

- McSAFER Experimental facilities:

COSMOS-H (KIT)

Codes	COSMOS-H		
	KIT	LUT	UJV
CFD	CFX	OpenFOAM	CFX
SubCH	SCF		VIPRE
SysTH	TRACE		RELAP3D

MOTEL (LUT)

Codes	MOTEL				
	KIT	LUT	UJV	UPM	TBL
CFD	CFX		FLUENT		
SubCH			VIPRE		COBRA-TF
SysTH		APROS		TRACE	

HWAT (KTH)

Codes	HWAT	
	KTH	UPM
CFD	OpenFOAM	
SubCH		
SysTH	GOTHIC/TRACE	TRACE



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022

Challenges II: Core Physics

- Small size (H, D), heterogeneity
- Harder spectrum
- Increased role of reflector design
- Increased leakage from core
- Boron free cores:
 - Need innovative control rod design
 - Optimized shutdown reactivity
 - Reduced reactivity swing over the cycle
 - Etc.
- → Innovations needed to improve economics and keep high safety




McSAFER Solution Approach:


- Industrial use:
 - Point Kinetics + 3D nodal diffusion e.g. ANTS/SCF, PANTHER/TRACE, SIMULATE/S3K, PUMA/SCF, DYN3D/ATHLET
- Advanced research tools:
 - Transport deterministic solvers e.g. **PARCS-SP3/SCF, APOLLO3/FLICA WIMS/ARTHUR, DYN3D-SP3/SCF**
- High-fidelity MC-based tools
 - Coupled MC / subchannel codes e.g. **Serpent2/SCF**





KSMR and CAREM Transient Analysis with PARCS/SCF



KSMR Rod Ejection Accident with Pin Power Reconstruction at power peak



KSMR REA: Relative power evolution [%]



CAREM Cold Water Transient: Power and core inlet temperature evolution



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



Challenges III: 3D Thermal hydraulic phenomena in RPV



Challenges:

- Many components located inside the RPV
 - Pumps: e.g. SMART (8)
 - Helical HX e.g. SMART(8), CAREM (12)
 - PZR
- Additional structures to enhance mixing inside RPV (get uniform thermal hydraulic conditions at core inlet, relevant in case of SLB-accidents)
 - SMART design



Consequences:


- Flow patterns inside RPV perturbed by structures
- Mixed convection flow
- 3D flow conditions
- 1D thermal hydraulic codes are not able to properly describe these conditions

McSAFER Solution Approach:


- Industrial tools:
 - 1D / 3D coarse mesh TH codes
- Research tools:
 - Multiscale coupling of system TH with subchannel-codes
 - Multiscale coupling of system TH with CFD-codes



JRC: NuScale from 1D to 3D Thermal Hydraulics (TRACE)



1D TRACE Plant Model



1D/3D TRACE Plant Model




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022

McSAFER Multiscale/Multiphysics Tools: RPV and Plant Analysis



- 1 Interface between TRACE and CFD
- 2 Interface between TRACE and SCF
- 3 Interface between CFD to SCF

■ RPV multiscale approach for improved thermal hydraulic simulations:

System TH: TRACE, ATHLET, RELAP5-3D, APROS

Core TH: system TH, subchannel codes: SCF, VIPRE, ARTHUR, COBRA-TF

CFD e.g. OpenFOAM, TrioCFD, FLUENT

Core neutronics: Point kinetics, 3D Diffusion solvers




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.




20. IAEA TWG FPT Meeting. April, 5-6. 2022


UPM: NuScale Multiscale TH by TRACE/Subchanflow



3D RCS model




3D Cartesian VESSEL approach:
VESSEL Channels/FA ratio = 1:1



UPM 1D/3D NuScale Model

TRACE-SCF coupling scheme developed by KIT is applied in the UPM multiscale approach




UPM: TRACE 3D-SCF NuScale Model



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



HZDR: NuScale Multiscale TH: ATHLET/TrioCFD



NuScale SMR: 1D/3D Thermal Hydraulics Model

TrioCFD Model of Downcomer and lower plenum




This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.





20. IAEA TWG FPT Meeting. April, 5-6. 2022

UJV: NuScale Multiscale Thermal Hydraulic Model



ATHLET Thermal Hydraulics Model



FLUENT: 3D Thermal Hydraulics model of downcomer and lower plenum



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022

Challenges IV: Integral Plant Analysis under postulated DBA



Challenges:

- Many components located inside the RPV
 - Pumps: e.g. SMART (8)
 - Helical HX e.g. SMART(8), CAREM (12)
 - PZR
- Additional structures to enhance mixing inside RPV (get uniform thermal hydraulic conditions at core inlet, relevant in case of SLB-accidents)
 - SMART design



Consequences:


- Flow patterns inside RPV perturbed by structures
- Mixed convection flow
- 3D flow conditions
- 1D thermal hydraulic codes are not able to properly describe these conditions

McSAFER Solution Approach:


- Industrial tools:
 - 1D / 3D coarse mesh TH codes
- Multiphysics / multiscale approach:
 - Coupling of systemTH/Subchannel and 3D Diffusion solvers e.g. TRACE/PARCS/SCF
 - SystemTH/Subchannel and 3D Diffusion solvers e.g.
 - TRACE/PARCS/OpenFOAM
 - ATHLET/DYN3D/TrioCFD
 - TRACE/ANTS/OpenOFAM
 - ATHLET/DYN3D/FLUENT




KIT Analysis Approach: TRACE/PARCS/OpenFOAM



TRACE Domain: Core + RPV + Plant



TRACE Domain: Core + RPV



OpenFOAM Domain

ICoCo-based TRACE-OpenFOAM and PARCS/TRACE coupling



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022

McSAFER Education & Training, Dissemination




- Training courses:
 - First training course on SMR Technologies: January 25-27.2021: UPM
 - Participants: 194
 - Second training course on SMR neutronics and thermal hydraulics: March 22-24, 2022: LUT
 - Lectures on simulation methods, Demonstration of Kraken Multiphysics framework, TH laboratory activities
 - Participants:
 - 17 students at LUT,
 - total 44 incl. lecturers and online participants (first day was streamed)
 - MOOC course on Multiphysics simulations applied to SMR (march 2023): UPM
- Mobility program
 - 9 fellowships **to be assigned for mobility of young researchers**
 - See: <https://mcsafer-h2020.eu/news-and-events/>
 - Still SEVEN fellowships available!



McSAFER Coordinator



Contact:
Victor.sanchez@kit.edu
Handy: +49 15201547532
KIT CN Karlsruhe



Visit website: www.mcsafer-h2020.eu



This project has received funding from the Euratom research and training programme 2019-2020 under grant agreement No 945063.



20. IAEA TWG FPT Meeting. April, 5-6. 2022