



Corrigendum

Corrigendum to “Robust and efficient electroreduction of CO₂ to CO in a modified zero-gap electrochemical cell” [Chem. Eng. J. 509 (2025) 161119]

Siyu Zhong^{a,*}, Pengfei Sui^b, Peter Holtappels^a, Alexander Navarrete^a, Fengwang Li^c, Roland Dittmeyer^{a,*}

^a Institute for Micro Process Engineering (IMVT), Karlsruhe Institute of Technology (KIT), Hermann-von-Helmholtz-Platz 1, 76344 Eggenstein-Leopoldshafen, Germany

^b Department of Chemical and Materials Engineering, University of Alberta, 9211 116 Street NW, Edmonton, Alberta T6G 1H9, Canada

^c School of Chemical and Biomolecular Engineering and ARC Centre of Excellence for Green Electrochemical Transformation of Carbon Dioxide, University of Sydney, Sydney, NSW, Australia

The Faradaic efficiency (FE) of products was calculated by this equation:

$$FE = \frac{Q_i}{Q_{total}} \times 100\% = \frac{n \times v \times x \times \frac{Fp}{RT}}{I} \times 100\%$$

DOI of original article: <https://doi.org/10.1016/j.cej.2025.161119>.

* Corresponding authors.

E-mail addresses: siyu.zhong@kit.edu (S. Zhong), roland.dittmeyer@kit.edu (R. Dittmeyer).

<https://doi.org/10.1016/j.cej.2025.163103>

Available online 6 May 2025

1385-8947/© 2025 The Author(s). Published by Elsevier B.V. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).